

rainbow® DCI®-mini Sensor

Spot-check Monitoring Sensor Featuring Masimo SET® Measure-through Motion* and Low Perfusion™ Pulse Oximetry



Pulse Oximetry




SpO₂



PR

Pulse Rate*



PI

Perfusion Index

rainbow®



SpHb®

Total Hemoglobin**

- > Small, lightweight reusable sensor with flexible cable allows for sensor stability and patient comfort during monitoring
- > The combination of noninvasive hemoglobin and SpO₂ measurements on a single sensor enables use in a variety of clinical settings
- > rainbow SET® Pulse CO-Oximetry measures multiple physiologic parameters, providing more information than traditional pulse oximetry

* Masimo SET® Measure-through Motion technology includes SpO₂ and PR. ** SpHb indicated for adult patients only.

Sensor Application

Adult Patient
≥30 kg



Finger Application

Pediatric Patient
10-50 kg



Finger Application



Great Toe Application

Comes with an easy-to-use finger gauge for proper sensor site selection

rainbow® DCI-mini Sensor Specifications

ACCURACY

	70-100%
Oxygen Saturation (%SpO ₂) Accuracy Range.....	70-100%
No Motion Adults/Pediatrics (ARMS) ¹2%
Motion Adults/Pediatrics (ARMS) ¹3%
Low Perfusion Adults/Pediatrics (ARMS) ¹2%
Pulse Rate (PR) Accuracy Range	25-240 bpm
No Motion Adults/Pediatrics (ARMS) ¹	3 bpm
Motion Adults/Pediatrics (ARMS) ¹	5 bpm
Low Perfusion Adults/Pediatrics (ARMS) ¹	3 bpm
Total Hemoglobin (SpHb) Accuracy Range	8-17 g/dL
Upper 95% LoA ²	2.07
Lower 95% LoA ²	-1.82

WEIGHT RANGE

Adult.....	>30 kg, Finger or Toe Application
Pediatric*.....	10-50 kg, Finger, Thumb, or Great Toe Application

COMPATIBILITY

rainbow® DCI-mini reusable sensors are for use with devices containing Masimo rainbow SET technology (v7.4 or higher) or licensed to use rainbow® compatible sensors. SpHb parameter must be on the device.

ORDERING INFORMATION

Non-sterile / Packaged 1 per box with Finger Gauge / Does not contain natural rubber latex Sensor	Part Number
rainbow® DCI-mini, 400 Spot-checks.....	3798
rainbow® DCI-mini, 1000 Spot-checks.....	3799

¹ ARMS accuracy is a statistical calculation of the difference between device measurements and reference measurements. Approximately two-thirds of the device measurements fell within \pm ARMS of the reference measurements in a controlled study. ² The differences between measurements by the two methods are used to calculate the mean and standard deviation. The lower 95% limit of agreement is the mean minus 1.96 standard deviation and the upper 95% limit of agreement is the mean plus 1.96 standard deviation. These limits are expected to contain 95% of the differences between measurements between the two methods in controlled environments. Accuracy testing for SpHb was performed on healthy and sick subjects.

* SpHb indicated for adult patients only.

SpHb monitoring with rainbow® DCI-mini is not intended to replace laboratory blood testing. Blood samples should be analyzed by laboratory instruments prior to clinical decision making.

SpHb with rainbow® DCI-mini is not intended for use on pediatric patients, pregnant patients, and patients with renal disease.

Caution: Federal (USA) law restricts this device to sale by or on the order of a physician. See instructions for use for full prescribing information, including indications, contraindications, warnings, and precautions.

Masimo U.S.
Tel: 1 877 4 Masimo
info-america@masimo.com

Masimo International
Tel: +41 32 720 1111
info-international@masimo.com

