rainbow Acoustic Monitoring

Noninvasive and continuous monitoring of acoustic respiration rate



The respiratory signal is separated and processed using acoustic signal processing that leverages Masimo Signal Extraction Technology (SET[®]) to display continuous respiration rate (RRa[®]) and an acoustic respiration waveform, a visualization of the acoustic signal caused by the patient's airflow.




- Clinicians have the option to use the acoustic sensor to listen to the sound of a patient's breathing remotely from a Masimo Patient SafetyNet^{**} view station.
- An adhesive Respiratory Acoustic Sensor (RAS) detects acoustic signals produced by the turbulent airflow in the upper airway that occurs during inhalation and exhalation, while signal processing algorithms convert the acoustic patterns into breath cycles to calculate respiration rate.
- Continuous monitoring of SpO2 and RRa, as well as other physiologic parameters, on a single Masimo Pulse CO-Oximeter[®], provides clinicians with more data to make informed care decisions and helps facilitate well-rounded patient assessment.



The Need for Continuous Respiration Monitoring

Respiratory rate (RR) is one of the most sensitive markers of a patient's condition and a vital component of clinical assessment and monitoring. Doctors use a number of methods to assess RR.¹


Neonatal intensive care unit (NICU) patients (neonates) need continuous monitoring of vital signs such as respiration rate without being caused discomfort or irritation.² Respiratory conditions are the most common reason for admission to a neonatal unit in both term and preterm infants.³



RAS-45 Infant/Neonatal Sensor

- Small size with a chest application site away from the face allows for continuous respiratory rate monitoring without interfering with daily care activities, such as feeding, holding, bathing, and supine positioning.
- Customizable neonatal profiles on Masimo devices automatically configure monitoring ranges and alarm thresholds to the most applicable settings for the patient population, simplifying nursing workflows.

In a study of 40 pediatric patients (12 months to 18 years of age) undergoing post-anesthesia care, in which researchers compared acoustic respiration rate monitoring using RRa to nasal capnography, impedance pneumography, and a reference method (counting breaths), researchers found that the difference in bias and precision between RRa and capnography was not significant, but that 97.5% of the patients (39) demonstrated good tolerance of the acoustic sensor, whereas 62.5% (25) demonstrated good tolerance of the nasal cannula. The researchers concluded, "Continuous respiration rate measurement from noninvasive, acoustic monitoring showed good agreement with nasal capnography, but was much better tolerated in post-surgical pediatric patients. Acoustic monitoring has the potential to increase the safety of pediatric patients by providing a reliable and accurate method for the continuous monitoring of respiration rate."4



Pediatric Patient

15 out of 40 pediatric patients removed the nasal cannula while only one removed the rainbow' acoustic sensor.⁴




RAS-45 Adult/Pediatric Sensor

- Continuous respiration rate monitoring of patients with RRa may provide clinicians with an indication of changes in respiration or incidence of respiratory pause.
- Small size with thin, flexible adhesive allows for comfortable application on patients with smaller necks or fragile skin.



RAS-125 Sensors



- Breathable cloth allows air to penetrate tape for enhanced adhesion on adult and pediatric patient, including diaphoretic patients
- Also available in a short-term monitoring sensor option



RAS-125c

RAS Specifications

ACCURACY – (A _{RMS}) ⁵	INFORMATION	
RAS-125c/RAS-45 Breaths per Minute (bpm), Accuracy Range (Adult/Pediatric)	Single-use / Non-sterile / Packaged 10 per box / Does not contain natural rubber latex ORDERING INFORMATION	
	RAS Sensor† Part Number	
WEIGHT RANGE	RAS-45 (Adult/Pediatric)	4171
RAS-45 (Adult/Pediatric) >10 kg, neck application RAS-45 (Infant/Neonatal) <10 kg, chest application	RAS-45 (Infant/Neonatal)	4425 .3475
COMPATIBILITY		
Compatible OximetersSystems containing Masimo rainbow SET® or licensed to use rainbow Acoustic Monitoring® sensors		

*The use of the trademark Masimo PATIENT SAFETYNET is under license from University Health System Consortium. † Requires RAM Dual Cable to obtain RRa measurement.

¹ Keir et al. J Clin Monit Comput. (2015) 29:455 -460. DOI 10.1007/s10877-014-9621-3. ² Abbas et al. *BioMedical Engineering OnLine*. 2011, 10:93. ³ Pramanik AK et al. *Pediatr Clin North* Am. 2015; 62: 453 -469. ⁴ Patino M et al. *Pediatric Anesthesia*. 2013, no. 12: 1166-1173. ⁵ A_{RMS} accuracy is a statistical calculation of the difference between device measurements and reference measurements. Approximately two-thirds of the device measurements fell within ± A_{RMS} of the reference measurements in a controlled study. ⁶ Respiration rate accuracy for the rainbow Acoustic Monitoring sensor and device has been validated for the range of 4 to 70 breaths per minute in bench top testing. Clinical validation was performed with the rainbow* Acoustic Monitoring sensors and monitoring devices for up to 30 breaths per minute in adult subjects (>30kg) and up to 50 breaths per minute in pediatric subjects (>10kg). ⁷ Respiration rate accuracy for the RAS-45 Inf/Neo sensor has been validated for the range of 4 to 120 breaths per minute in bench top testing. Clinical validation was performed with the RAS-45 Inf/Neo sensor and monitoring device for up to 82 breaths per minute in infant and neonatal subjects.

Caution: Federal (USA) law restricts this device to sale by or on the order of a physician. See instructions for use for full prescribing information, including indications, contraindications, warnings, and precautions.

Masimo U.S. Tel: 1 877 4 Masimo info-america@masimo.com Masimo International Tel: +41 32 720 1111 info-international@masimo.com

